

SUMMARY OF CROOKED CREEK WATERSHED ASSESSMENT IONIA, MICHIGAN

BY: MELANIE, STUDENT ASSISTANT
AND JANICE TOMPKINS, SENIOR WATER QUALITY ANALYST
FIELD OPERATION SECTION
WATER DIVISION

INTRODUCTION

The Crooked Creek watershed is located in the central-west portion of Ionia County. DESCRIPTION: It originates halfway between Portland and Clarksville in a primarily suburban, agricultural, and forested area and flows north towards the eastern edge of Saranac where it joins the Grand River. Michigan Department of Environmental Quality (MDEQ) field staff surveyed road/stream crossings within the watershed to quickly assess the health of the watershed. The survey combined both qualitative and quantitative assessment of Crooked Creek and its tributaries and provided a basis upon which to identify any potential sources of non point source pollution negatively affecting the watershed. In total, 6 road/stream crossing locations were surveyed during the assessment of the Crooked Creek Watershed. Refer to Attachment A, Road Stream Crossings Inventory for a summary of the survey locations conducted during September and October of 2004, as well as survey location maps. Site identification codes were developed using four letter identifiers for the subwatershed followed by the two digit site location number. Sites were numbered successively from the mouth to the headwaters.

METHODS

The DEQ's stream crossing watershed survey procedure was developed as a quick screening tool to assess general water quality and possible pollutant sources, causes and problems within the watershed. The survey procedure provides standardized visual assessments that can be conducted by DEQ staff or trained volunteers. Only observations that can be made from the road stream crossings are recorded; recording "educated guesses" or suspicions is prohibited. Because this assessment is based on visual observations, designed to be conducted quickly and by many different types of people and knowledge backgrounds, the survey results are only qualitative in nature.

A minimum of 30% of the road stream crossings within a watershed are to be surveyed with attention given to balanced geographical coverage and assessment across major land use changes and possible pollutant sources. Surveys are always conducted in one general direction (either upstream to downstream OR downstream to upstream), and the attempt is made to keep the surveyors and weather conditions consistent to limit bias and subjectivity between surveyors. This survey was conducted from the upstream to downstream direction and was completed in one day by two DEQ field staff. The right and left bank designations are always assigned based on looking downstream at each road stream crossing location.

At each survey location the following stream conditions are visually assessed:

- Weather and any event conditions
- Culvert/bridge conditions
- Channel conditions (width, depth, high water mark, riffles, pools, natural, maintained, recovering)
- Stream appearance (color, turbidity, algae, aquatic plants, trash, oil sheen, bacteria, foam)
- Substrate composition (boulder, gravel, silt, sand, unknown)
- In-stream Cover (undercut banks, overhanging vegetation, woody debris, pools, boulders, plants)
- Stream corridor (riparian vegetation type and width, bank erosion, canopy cover, adjacent land use)
- Potential Pollutant Sources (source and pathway identification)

At each survey location the following stream conditions are directly measured:

- Water temperature
- Dissolved oxygen content
- pH
- flow velocity
- latitude and longitude coordinates (GPS)

In addition each site was photo-documented with a digital picture taken in the downstream direction, upstream direction and of the road crossing. Refer to the DEQ's *Stream Crossing Watershed Survey Procedure* for further information and a complete description of the above conditions.

OBSERVATIONS

Water Temperature, pH, and Dissolved Oxygen

Survey locations were assessed in the order of upstream sites (in the headwaters) to downstream sites (towards the mouth). 6 locations were measured for temperature, DO, and pH. pH values ranged from 7.12 to 7.97, which were not outside of the normal range for streams within Michigan. Overall the average temperature was 48°F. Normal stream temperatures capable of supporting a coldwater fishery with few diseases are below 57°F. Walleye, northern pike and some trout are adapted to temperatures between 57° to 68°F while temperatures over 68°F are characteristic of fish communities characterized by bass, crappie, bluegill, carp and sucker with occurrence of fish disease high. While temperatures recorded here seem low it is important to note that this survey was not conducted during the hottest summer months when temperature becomes a limiting factor to some species. Temperatures will appear cool because the survey was conducted during the fall. The average dissolved oxygen content is 8.02 ppm; it varies from 10.60 ppm at station CROO-04 to a measurement of 5.21 ppm at CROO-01 where there is very low flow. The dissolved oxygen requirement for native bass and crappie growth and well-being is 5 ppm and for trout it is at least 6 ppm. Given the relatively high average oxygen content, at most locations, Crooked Creek is a comfortable environment for aquatic life. Refer to Figure 1, which depicts the temperature, pH, and DO levels at all locations.

Substrate

Substrate was observed and quantified for both the upstream and downstream stretch at each survey location. In all, 12 substrate observations were recorded at 6 locations. Substrate type is important when considering habitat suitability for desired species within the system (i.e. trout and other fish species). Cobble and gravel substrate with a low degree of embeddedness are the most suitable for reproduction in many fish species and is important for macro invertebrates as well. Evidence of silt and sand dominated substrate could indicate problems within the watershed such as erosion and sedimentation. Among the survey locations within the Crooked Creek Watershed, approximately 1/3 were dominated (50 to 100% covered) by sand, 17% were dominated silt, detritus or muck, and no sites were dominated by gravel. 50% of the sites were unable to be categorized due to turbidity or other factors (note: some sites had equal amounts of sand and silt). Refer to Figure 2 for a graph depicting the substrate composition for those survey locations located along Crooked Creek.

In-Stream Cover

The presence of in-stream cover was assessed at each location for both the upstream and downstream stretches. In-stream cover, such as overhanging vegetation, undercut banks, deep pools, boulders, plant cover and large woody debris provide habitat for macro invertebrates and aquatic organisms such as amphibians and fish. Of the 12 observations made, 11 of the sites had overhanging vegetation and woody debris; 50% of the sites had undercut banks and boulders. Deep pools and aquatic plant cover were each found in approximately 42%, and 33% of the sites respectively. Refer to Table 1 for a summary of the in-stream cover observations made at each survey location.

Physical Appearance

The physical appearance of the stream at each survey location was assessed based on the presence or absence of aquatic plants, floating algae, filamentous algae, bacterial slimes, turbidity, oil sheen, foam and/or trash. In all, 12 sites were assessed for physical appearance; observations were recorded and rated as either present or abundant. No oil sheens, turbidity, or filamentous algae were observed at any of the sites. There were a one instance each for foam and bacterial slime. Approximately 25% of the sites exhibited some trash, 33% of the sites had some floating algae, and 42% exhibited aquatic plants (including duckweed). Refer to Table 2 for a summary of the physical appearance observations made for each survey location.

Stream Corridor

The width of riparian vegetation was assessed at each survey location for the both the right and left banks of the upstream and downstream stretches. The presence of riparian vegetation reduces the amount of surface water runoff to streams, provides a filter strip for nutrients within runoff waters, provides overhanging vegetation for stream habitat, provides a source of woody debris, stabilizes stream banks against erosion and determines the availability of sufficient stream canopy cover for temperature regulation. 6 survey locations were assessed, resulting in 24 observations of riparian vegetation width recorded. The observations fell mostly into three width categories: 33% had less than 10 feet, 25% had between 10 and 30 feet, and 33% had over 100 feet of riparian vegetation. Only two sites fit into the 30-100 feet category. The streamside land cover, estimated bank erosion and percent stream canopy were evaluated at each of the 6 survey locations for both the upstream and downstream stretches. In all, 12 observations were made for each of the above listed characteristics. Of the survey locations, 50% were recorded as having streamside land cover predominantly shrubs, 25% predominantly grasses, and 25% were dominated by trees. In general, vegetation such as grasses and shrubs and residential and agricultural land uses, are associated with narrow riparian widths. More extensive riparian vegetation is usually associated with forests and old fields. Overall erosion of the banks was a slight to moderate problem in the Crooked Creek Watershed with approximately 33% of the sites described as having moderate bank erosion. Refer to Table 3 for the distribution of riparian width and vegetation observations made for both the right and left bank at each survey location.

Stream canopy cover is important for providing shade and maintaining cool temperatures within the stream. Cooler temperatures also helps keep dissolved oxygen levels from depleting, an important habitat requirement for many fish species and other aquatic organisms. Of the 12 sites assessed, 4 had less than 25% cover, 4 had between 25 and 50% cover and 4 had over 50% cover.

Adjacent Land Uses

Adjacent land uses were recorded at each survey location for both the upstream and downstream stretches as well as both the right and left banks. Because the entire section of stream that can be seen from the road crossing is evaluated, multiple land uses can be recorded for each site. Land uses within the watershed play an important role in nutrient input, erosion, and in-stream conditions that affect water quality, quantity and habitat. Refer to Table 4 and Figure 3 for a summary of all the adjacent land uses recorded within the watershed. The most common adjacent land uses were maintained lawn, shrub/old field, and forest followed by a lesser number of observations for pasture, impervious surfaces, cropland lawns, and wetlands.

Potential pathways of non-point source pollution

During the completion of the road stream crossing surveys, field staff also evaluated the *potential* for non point source pollution. This assessment focuses on the severity of potential pollutant *inputs*, not pollutant *impacts*. As part of this evaluation process field staff look for 1.) a possible pollutant source, 2.) a potential pathway to the water body and 3.) potential severity of the input. Because each potential source was given a ranking of slight, moderate and high for severity, the values recorded were weighted before they were summed for each category (Refer to Figure 4). Observations recorded as slight were considered to be the basis for comparison, therefore observations recorded as moderate were multiplied by 1.5 and observations recorded as high were multiplied by 2. In Crooked Creek, the potential non point source pollution from transportation, riparian vegetation removal, and bank erosion were the most serious while urban/residential runoff, hydrology, grazing, and upstream impoundment related sources were also considered possible sources of NPS pollution. Refer to Table 5 for a summary of the non point source pollution observations identified for each survey location.

RESULTS

Crooked Creek originates in the agricultural fields northwest of Ionia. Stations in along Crooked Creek are denoted by CROO prefixes. The land use in this area is dominated by agriculture use with low density residential use and dispersed forest. Refer to Attachment C for site photos and to Attachment D for site survey forms. The following conditions and comments were recorded on the survey forms:

CROO-01: Peck Lake Rd. east of Hartwell Rd.

Water temperature was 48° F, pH was 7.12, and the DO was recorded as 5.21 ppm. Substrate observations were prohibited. Overhanging vegetation, woody debris, and aquatic plants were available for in-stream cover. Abundant aquatic plants and floating algae were observed. Moderate to abundant riparian vegetation width was available. Shrubs made up the land cover. Adjacent land uses included maintained lawn and wetlands. Potential non point source pollution (NPS) was categorized as slight for transportation, upstream impoundment, and hydrology. Comments were: *No specific comments were recorded for this site.*

CROO-02: Bennett Rd. east of Hartwell Rd.

Water temperature was 47° F, pH was 7.56, and the DO was recorded as 7.16 ppm. Substrate observations were prohibited. Deep pools, woody debris, and aquatic plants were available for in-stream cover. Abundant aquatic plants

and floating algae were observed. Variable riparian vegetation width was available. Grasses and shrubs made up the land cover. Adjacent land uses included shrub/old field, pasture, and cropland. Potential non point source pollution (NPS) was categorized as slight for transportation and bank erosion, moderate for crops, and high for grazing and riparian vegetation removal. Comments were: *Cattle have unrestricted access to upstream side of crossing; visible impact along stream; electrical fence west of stream on upstream side.*

CROO-03: David Hwy west of Harwell Rd.

Water temperature was 48° F, pH was 7.82, and the DO was recorded as 8.92 ppm. Sand appeared to dominate the substrate with lesser amounts of silt and gravel also present. Overhanging vegetation, woody debris, and undercut banks were available for in-stream cover. No aquatic plants, floating algae, filamentous algae, turbidity, bacterial sheen/slime, oil sheen, foam or trash were observed. Variable riparian vegetation width was available. Trees and grasses made up the land cover. Adjacent land uses included shrub/old field, forest, and maintained lawn. Potential non point source pollution (NPS) was categorized as slight for transportation and downstream bank erosion and moderate for riparian vegetation removal and upstream bank erosion. Comments were: *Some bank erosion; major residential landscaping downstream with no silt fences.*

CROO-04: David Hwy east of Bliss Rd.

Water temperature was 48° F, pH was 7.97, and the DO was recorded as 10.6 ppm. Sand and silt appeared to dominate the substrate with lesser amounts of gravel also present. Overhanging vegetation, deep pools, boulders, woody debris, and undercut banks were available for in-stream cover. Some aquatic plants, bacterial slime, and trash were observed. Little to moderate riparian vegetation width was available. Grasses and shrubs made up the land cover. Adjacent land uses included shrub/old field, maintained lawn, and impervious surfaces. Potential non point source pollution (NPS) was categorized as slight for transportation, downstream riparian vegetation removal and moderate for upstream riparian vegetation removal and urban/residential runoff. Comments were: *No specific comments were recorded for this site.*

CROO-05: David Hwy west of Bliss Rd.

Water temperature, pH, and DO measurements were prohibited. Sand appeared to dominate the substrate with lesser amounts of silt, gravel, and boulder also present. Overhanging vegetation, deep pools, boulders, woody debris, and undercut banks were available for in-stream cover. No aquatic plants, floating algae, filamentous algae, turbidity, bacterial sheen/slime, oil sheen, foam or trash were observed. Little to moderate riparian vegetation width was available. Shrubs made up the land cover. Adjacent land uses included shrub/old field, forest, and maintained lawn. Potential non point source pollution (NPS) was categorized as slight for transportation, riparian vegetation removal, urban/residential runoff, and upstream bank erosion and moderate for downstream bank erosion. Comments were: *Some bank erosion; bridge concrete is old and cracking; downstream is perched unable to confirm distance of drop.*

CROO-06: David Hwy east of Jackson Rd.

Water temperature was 49° F, pH was 7.90, and the DO was recorded as 9.15 ppm. Sand and silt appeared to dominate the substrate with lesser amounts of gravel and boulders also present. Overhanging vegetation, boulders, woody debris, and undercut banks were available for in-stream cover. Some foam and trash were observed. Variable riparian vegetation width was available. Trees made up the land cover. Adjacent land uses included shrub/old field, forest, maintained lawn, and impervious surfaces. Potential non point source pollution (NPS) was categorized as slight for transportation, riparian vegetation removal, urban/residential runoff, hydrology, and downstream bank erosion and moderate for upstream bank erosion. Comments were: *Significant trash in road ditch washing towards stream; upstream bank cutting to misalign with the box culvert.*

The majority of the impacts to the stream in this area seem to result from transportation erosion or erosion due to the road stream crossing (sand/gravel roads, road washout). Crop related sources and urban/residential runoff also account for some pollution in this tributary to the Grand River.

